

OFC-1200 P and OFC-1200 G Offset Dish



Parameter	Unit	Numerical	Reflector Material:	
Effective Reflector Size	mm	1190x1298	Glass Epoxy Metallised Composite (resistant to salt, air pollution)	
Operating Frequency	GHz	10.7÷12.8		
Gain (for frequency in GHz)	10,7	dBi	40,9	Colour: light grey (RAL 7047)
	11,3	dBi	41,1	
	12,6	dBi	42,1	
3dB Beamwidth (for frequency in GHz)	10,7	deg	1,6	Package Size (outside dimensions): 1÷2 units in Cardboard Box 1340x170x1240 mm
	11,3	deg	1,5	
	12,6	deg	1,4	
Focal Length	mm	700,0	Compatible Accessories: OFZ-1200 Elevation over Azimuth Mount	
Offset Angle	deg	23,5		
Feed Clamp Diameter	mm	40,0	Wind Loading:	
Weight Reflector OFC-1200 P/1200 G	kg	6,7/8,5		Operational 80 km/h
Weight OFC-1200 P/OFC-1200 G include Mount	Az-El	kg	8,5/10,3	Survival 200km/h
Power/Voltage electric anti-icing system (for OFC-1200 G only)	W	180	Operating Temperature:	Operational -40 ÷ 60
	V	AC 230		Survival -50 ÷ 80



LAMINAS Spółka z o.o.

38-430 MIEJSCE PIĄSTOWE al. Dworska 50

Tel./fax: +48 134 362 067

Internet: www.laminas.com.pl

e-mail: laminas@laminas.com.pl